

# ANPx101/NUM(+)

closed loop, linear, horizontal stepper positioner with optoelectronic encoder

## Technical Specifications

|  |   |                                       |                                    |
|--|---|---------------------------------------|------------------------------------|
| <b>Technology</b>                            |   | <b>Compatibility with Electronics</b> |                                    |
| travel mechanism                             | inertial piezo drive                        | ANC350 piezo positioning controller   | ANC350/NUM                         |
| <b>Size and Dimensions</b>                   |   | <b>Working Conditions</b>             |                                    |
| footprint; height                            | 24 x 28; 11.5 mm                            | mounting orientation                  | axis horizontal                    |
| maximum size                                 | 29 x 28; 11.5 mm                            | magnetic field range                  | 0 .. 7 T                           |
| weight                                       | 25.5 g                                      | temperature range (/RT, /HV, /UHV)    | 0 .. 100 °C                        |
| <b>Coarse Positioning Mode</b>               |   | max. bake out temperature (/UHV)      |                                    |
| <b>@ 300 K</b>                               |   | 150 °C                                |                                    |
| input voltage range                          | 0 .. 60 V                                   | minimum pressure (/RT)                | 1E-4 mbar                          |
| typical actuator capacitance                 | 1.11µF                                      | minimum pressure (/HV)                | 1E-8 mbar                          |
| travel range (step mode)                     | 5 mm  | minimum pressure (/UHV)               | 5E-11 mbar                         |
| typical minimum step size                    | 50 nm                                       | <b>Position Encoder</b>               |                                    |
| maximum drive velocity                       | ≈ 3 mm/s                                    | readout mechanism                     | optoelectronic: /NUM & /NUM+/(U)HV |
| <b>Fine Positioning Mode</b>                 |   | sensor power (when measuring)         | /NUM: 300 mW & /NUM+/(U)HV: 50 mW  |
| <b>@ 300 K</b>                               |   | encoded travel range                  | full travel                        |
| input voltage range                          | 0 .. 100 V                                  | wavelength of illumination            | 870 nm                             |
| fine positioning range                       | 0 .. 5 µm                                   | sensor resolution                     | 10 nm                              |
| fine positioning resolution                  | sub-nm                                      | repeatability                         | 50 nm                              |
| <b>Materials (non-magnetic)</b>              |   | linearity (over full travel)          | < 0.01 %                           |
| positioner body                              | titanium (upgrade option: copper beryllium) | absolute accuracy                     | < 0.01 % of travel range           |
| actuator                                     | PZT ceramics                                | <b>Connectors and Feedthroughs</b>    |                                    |
| connecting wires                             | insulated twisted pair, copper              | <b>/RT Versions</b>                   | <b>all /HV, /UHV Versions</b>      |
| <b>Load (@ ambient conditions)</b>           |   | connector type                        | 14-pole connector                  |
| <b>mounting orientation: axis horizontal</b> |   | electrical feedthrough solution       | ---                                |
| maximum load                                 | 1 N (100 g)                                 | 15-pin D-Sub connector                |                                    |
| maximum dynamic force along the axis         | 2 N   | VFT/HV, VFT/UHV                       |                                    |
| <b>Mounting</b>                              |   |                                       |                                    |
| from the top                                 | 2 through holes dia 2.2 mm, cntrbr. f. M2   |                                       |                                    |
| from the bottom                              | 2 threads M2.5 x 6 mm                       |                                       |                                    |
| load on top                                  | 6 threads M2 x 2.8 mm                       |                                       |                                    |
| <b>Article Numbers</b>                       |   |                                       |                                    |
| /RT version                                  | 1002655                                     |                                       |                                    |
| /HV version                                  | #   |                                       |                                    |
| /UHV version                                 | #   |                                       |                                    |

## Technical Drawings

